

## Product fiche according to Commission Regulation (EU) 1254/2014

a	Supplier name	Nuaire			
b	Model	MRXBOXAB-ECO-LP2			
С	Specific energy consumption and SEC class	Cold	Average	Warm	
	SEC (KWh/m <sup>2</sup> .a)	-83.6	-40.8	N/A	
	SEC Class	A+	Α .	N/A	
d	RVU or NRVU / Unidirectional or bidirectional	RVU	RVU / Bi-directional		
е					
_	Type of drive (multi-speed drive or variable speed drive)	Variable speed drive			
f	Type of heat recovery system (recuperative, regenerative,	Recuperative			
~	none) Thermal efficiency of heat recovery	N	79%		
g h	Maximum flow rate (m <sup>3</sup> /h)				
	Electric power input of the fan drive at maximum flow rate	281			
i	(W)	163			
i	Sound power level (LWA)	48			
k	Reference flow rate (m <sup>3</sup> /s)	0.0560			
ı	Reference pressure difference (Pa)	50			
m	Specific power input (SPI) (W/(m³/h))	0.288			
n	Control factor and control typology	0.65 based on boost by local light			
	control factor and control typology	0.65 based (	on boost by Io switches	ical light	
О	Maximum internal and external leakage rates (%)	< 5% Internal, <5% External			
р	Mixing rate of non-ducted bidirectional ventilation units not intended to be equipped with one duct connection on either				
	supply or extract air side		N/A		
q	Position and description of visual filter warning for RVUs				
	intended for use with filters, including text pointing out the				
	importance of regular filter changes for performance and	Refer to I&M instructions supplied			
	energy efficiency of the unit	with the unit			
r	For unidirectional ventilation systems, instructions to install				
	regulated supply/exhaust grilles in the façade for natural air				
	supply/extraction	N/A			
S	Internet address for pre-/dis-assembly instructions		www.nuaire.co.uk/disassembly		
_	For non-dusted units only the sixfley consitivity to process	<u>II</u>	<u>nstructions</u>		
t	For non-ducted units only: the airflow sensitivity to pressure variations at + 20 Pa and – 20 Pa	N/A			
u	For non-ducted units only: the indoor/outdoor air tightness in		N/A		
u	m³/h	N/A			
V	The annual electricity consumption (AEC) (in kWh		N/A		
•	electricity/a)		1.52		
W	The annual heating saved (AHS) (in kWh primary energy/a)	Cold	Average	Warm	
		87.4	44.7	N/A	

061131